



Hot Cold PVC Mixer 200L 500L High Speed Mixer For Plastic

Our Product Introduction

for more products please visit us on plasticextrudersmachine.com

Basic Information

- Place of Origin: Shandong, China
- Brand Name: Changyue
- Packaging Details: Export Film Packing / According To Customer
- Delivery Time: 15 Days (1 - 1 Pieces) To Be Negotiated (> 1 Pieces)



Product Specification

- Model NO.: 200/ 500 300/600 500/1000
- Warranty: 1 Year
- Model: 500/1000
- Mixing Time: 10 Minutes
- Suitable Material: PVC With Chemical
- Transport Package: Export Package
- Specification: 500/1000
- Trademark: CHANGYUE
- Origin: Qingdao, China
- HS Code: 84772090
- Supply Ability: 150 Kg/ Batch
- Package Size: 250.00cm * 200.00cm * 350.00cm
- Package Gross Weight: 2200.000kg
- After-sales Service: Site Installation
- Automatic Grade: Full-Automatic



More Images



Product Description

High Speed Hot Cold Mixer for PVC 200/500 L Return refunds Refund within 30 days

high speed hot cold mixer for PVC / PVC hot cold mixer

high speed hot cold mixer for pvc

PVC mixer

	100/200	200/500	300/600	500/1000	800/1600
Total volume	100/200	200/500	300/600	500/1000	800/1600
Effective volume	75/160	150/320	225/400	375/650	600/1050
Electric power (kW)	14/22/7.5	30/42/7.5	40/55/11	55/75/11	110/30
Heat-cooling method	Electric/self-friction/water cooling				
High speed	810/1000	810/1000	810/1000	810/1000	1100/1200
Motor power	14/22/7.5	30/42/7.5	40/55/11	55/75/11	110/30

	500/1600	800/2000	800/2500	1600/4000
Total volume	500/1600	800/2000	800/2500	1600/4000
Effective volume	330/1000	560/1400	600/1500	1120/2700
Electric power (kW)	55/75/11	110/30	110/30	110/30
Heat-cooling method	Electric/self-friction/water cooling			
High speed	1100/1200	1100/1200	1100/1200	1100/1200
Motor power	55/75/11	110/30	110/30	110/30

Горячий/Холодный смеситель

Основные технические параметры:

Модель	SRL-Z200/500	ASRL-Z300/600	ASRL-Z500/1000A
Полный объем (л)	200/500	300/600	500/1000
Действительный объем	150/320	225/380	375/640
Мощность двигателя (кВт)	30/42/5,5	40/55/7,5	55/75/11
Скорость перемешивания (об/мин)	480/970/130	475/950/130	500/1000/100
Тип отопления/охлаждения	электричество/самотрение/водяное охлаждение		
Время смешивания (мин)	6-10		
Время охлаждения (мин)	10-15		
Размер (мм)	4580×2240×2470	4725×2550×2643	4100×2800×2900
Вес (кг)	3400	4000	5400





Qingdao Changyue Plastic Machinery Co., Ltd.



0086 13705428176



edward@hualideplast.com



plasticextrudersmachine.com

SOUTH LONGYI ROAD, NO.2 JIAOXI INDUSTRIAL ZONE, JIAOZHOU CITY, QINGDAO, CHINA