



Customized 300Kg/H Geo Cell Line 600mm-1500mm HDPE Geocell Production Line

Basic Information

. Place of Origin: Shandong, China Brand Name: Changyue


CE, ISO9001:2008 · Certification:

 Packaging Details: Export Film Packing / According To

Customer

• Delivery Time: 15 Days (1 - 1 Pieces) To Be Negotiated (>

1 Pieces)



Product Specification


SJ 90 Model NO.:

Screw No.: Single-screw · Automation: Automatic Computerized . Computerized: · Customized: Customized

• Condition: New

PE Granules Raw Material: Motor Brand: Weg/Siemens • Inverter Brand: ABB/Delta • Machine Output: 300Kg/H Loading Port: Qingdao Port 600-1500mm . Sheet Width: . Sheet Thickness: 1-3mm

Export Film Packing / According To • Transport Package:



More Images









Product Description

Customized Geocell Making Machine HDPE Geocell Extruder Production Line at Qingdao Port

Product Description

HDPE sheet extrusion machine for Geocell

HDPE sheet production line for Geocell

HDPE sheet production line for Geocell

PP sheet / board extrusion machine / production line

HDPE / PP / ABS sheet extrusion machine / production line

HDPE sheet extrusion production line used for Geocell

PP sheet / board extrusion production line

PP/PE/ABS Sheet/Board Production Line

PP thermo forming sheet production line

Geocell sheet production line

PE sheet production line for geocell

Product Parameters

Equipment list

1.single screw extruder

2. Hydraulic mesh changing

3. Die mold

system
4.Electric control system

5. Three roller calender

6. Roll temperature regulator

7. Transmission and side

8.Haul off machine

cutting

10. Cutter

9. Length Measurement11. Extruder vacuum feeder

12. Driers

Summary

Suitable resin PP/PE/PS/ABS

Sheet width 400-2000mm(customized) Sheet thickness 0.2-2mm(as requirement)

Capacity 150-1000kg/h Power supply 380V 3phase 50HZ

Detailed Photos




1. drier & mixer volum: 1000 kg / 1500 kg

2. material: SS

- 1. vacuum auto loader
- 2. single screw extruder
- 3. one extruder or two extruder for single / multilayer sheet
- 4. exhausted screw
- 5. hydraulic mesh changer / filter & hydraulic station
- 6. T die: brand: JC times T die
- 7. sheet width: 600-300 mm
- 8. sheet thickness: 0.5-5 mm
- 9. main motor: Siemens Beide
- 10. melting pump if needed






- 2. roller diameter: 400 / 450 / 500 mm
- 3. flange type rotating jointor
- 4. roller temperature controlling unit
- 5. roller mirror treatment
- 6. Surface hardness: HRC55-58
- 7.Surface roughness: Ra<=0.025um
- 8. up & down movement by motor
- 9. the rollers can do embossment



2. transmission rollers: SS

3. slitting device: quantity according to requiremen





1. haul off: two rubber rollers

2. protection film lamination device

3. meter counter: Autonics from Korea



1. shear cutter

2. cutting width: according to requirement

3. cutting thickness: 1-5 mm





control panel

PLC control / not PLC control

inverter: ABB / Delta / according to customer requirement

contactor & relays: Siemens

switch: CHNT

touch screen: Siemens

PLC: Siemens





finished Geo cell

SLITTING AND ONLINE PUNCHING MACHINE



Certifications







After Sales

Service

1. After the machines are finished, the seller will test all machinesbefore shipment. If the buyer can not come to test

the machine,

we will test the machines and send the sample to buyer.

2..After shipment, the seller will send one or two technicians to the buyer's factory to help the buyer install the machine and

workers for buyer.

- 3. We will supply all electricity drawing, machine installation drawing.
- 4. When make shipment, we will put some spare electricity parts forfree, like the barrel hearers, thermcouples, breakers,

and other items which is easier broken.



Cingdao Changyue Plastic Machinery Co., Ltd.





edward@hualideplast.com



plasticextrudersmachine.com

SOUTH LONGYI ROAD, NO.2 JIAOXI INDUSTRIAL ZONE, JIAOZHOU CITY, QIGNDAO, CHINA