



200Kw Geocell Production Line 1220mm Wide HDPE Sheet **Extruders**

Basic Information

. Place of Origin: Shandong, China Brand Name: Changyue · Certification:

Export Film Packing / According To · Packaging Details:

Customer



Product Specification

SJ 90 Model NO.:

. Board Layers: Single Plate Screw No.: Single-screw Automation: Automatic · Computerized: Computerized Customized: Customized

• Condition: New

600-1200 Mm Sheet Width: . Sheet Thickness: 1-3 Mm 200Kw • Installation Power:

• Delivery Time: 15 Days (1 - 1 Pieces) To Be Negotiated (>

1 Pieces)

• Loading Port: Qingdao Port . Machine Output: 250 Kg/H

• Transport Package: Export Film Packing / According To



More Images









Product Description

US Design Geocell Production Line with Online Punching and Ultrasonic Welding Machine

Product Description

HDPE sheet extrusion machine for Geocell

HDPE sheet production line for Geocell

HDPE sheet production line for Geocell

PP sheet / board extrusion machine / production line

HDPE / PP / ABS sheet extrusion machine / production line

HDPE sheet extrusion production line used for Geocell

PP sheet / board extrusion production line

PP/PE/ABS Sheet/Board Production Line

PP thermo forming sheet production line

Geocell sheet production line

PE sheet production line for geocell

geocell production line with online punching machine

geocell making machine

Product Parameters

Equipment list

1.single screw extruder 2. Hydraulic mesh changing system

3. Die mold

4.Electric control system6. Roll temperature regulator

5.Three roller calender7. Transmission and side

cutting

8. Haul off machine

9. Length Measurement11. Extruder vacuum feeder

10. Cutter 12. Driers

Summary

Suitable resin PP/PE/PS/ABS

Sheet width 400-2000mm(customized)
Sheet thickness 0.2-2mm(as requirement)

Capacity 150-1000kg/h
Power supply 380V 3phase 50HZ

Detailed Photos



1. drier & mixer volum: 1000 kg / 1500 kg

2. material: SS

- 1. vacuum auto loader
- 2. single screw extruder
- 3. one extruder or two extruder for single / multilayer sheet
- 4. exhausted screw
- 5. hydraulic mesh changer / filter & hydraulic station
- 6. T die: brand: JC times T die
- 7. sheet width: 600-300 mm
- 8. sheet thickness: 0.5-5 mm
- 9. main motor: Siemens Beide
- 10. melting pump if needed






- 1. vertical three roller calender / 45degreee calender
- 2. roller diameter: 400 / 450 / 500 mm
- 3. flange type rotating jointor
- 4. roller temperature controlling unit
- 5. roller mirror treatment
- 6. Surface hardness: HRC55-58
- 7.Surface roughness: Ra<=0.025um
- 8. up & down movement by motor
- 9. the rollers can do embossment



1.cooling bracket length: 18 m

2. transmission rollers: SS

3. slitting device: quantity according to requiremen





1. haul off: two rubber rollers

2. protection film lamination device

3. meter counter: Autonics from Korea

1. shear cutter

2. cutting width: according to requirement

3. cutting thickness: 1-5 mm





control panel

PLC control / not PLC control

inverter: ABB / Delta / according to customer requirement


contactor & relays: Siemens

switch: CHNT

touch screen: Siemens

PLC: Siemens





finished Geo cell

Certifications







After Sales

Service

- 1. After the machines are finished, the seller will test all machinesbefore shipment. If the buyer can not come to test the machine,
 - we will test the machines and send the sample to buyer.
- 2..After shipment, the seller will send one or two technicians to the buyer's factory to help the buyer install the machine and train

workers for buyer.

- 3. We will supply all electricity drawing, machine installation drawing.
- 4. When make shipment, we will put some spare electricity parts forfree, like the barrel hearers, thermcouples, breakers, relays,

and other items which is easier broken.

Qingdao Changyue Plastic Machinery Co., Ltd. © 0086 13705428176 edward@hualideplast.com plasticextrudersmachine.com

SOUTH LONGYI ROAD, NO.2 JIAOXI INDUSTRIAL ZONE, JIAOZHOU CITY, QIGNDAO, CHINA