Our Product Introduction

昌岳塑机



One Feed PVC Plastic Water Supply Pipe Making Machine Full Intermeshing **Engagement System**

Basic Information

. Place of Origin: Shandong, China Brand Name: Changyue · Certification: ISO9001 CE

 Packaging Details: Export Film Packing / According To

Customer

• Delivery Time: 15 Days (1 - 1 Pieces) To Be Negotiated (>

1 Pieces)



Product Specification

Model NO.: SJSZ 65/132


 Plastic Processed: PVC

Product Type: Extrusion Molding Machine

• Feeding Mode: One Feed

· Assembly Structure: Separate Type Extruder

· Screw: Twin-Screw • Engagement System: Full Intermeshing Screw Channel Structure: Deep Screw • Exhaust: Exhaust Automation: Automatic Computerized Computerized: 300/600 • Mixer Model: Extruder Size: Sjsz 65/132 PVC Pipe Size: 50-200 Mm Loading Port: Qingdao Port, China



More Images









PVC pipe production line / **PVC** tube making machine

Description of PVC pipe makign machine

PVC pipe extruder machine/UPVC pipe making machine is mainly used in the manufacturer of the UPVC and PVC pipes with various tube diameters and wall thickness such as agricultural and constructional plumbing, water supply and drain etc. This set is composed of conical twin-screw extruder, vacuum calibration tank, hual-off machine, cutter, stacker etc. Our machine can produce the PVC pipe with diameter from 16-630mm.

Main parameter of PVC pipe making machine

Model	pipe range(mm)	extruders	max.speed(m/mi n)	total power(kw)	max.output(kg/ h)	line length(m)
PVC-50*2	16-50	SJSZ51/105	6	60	150	20
PVC-63	16-63	SJSZ45/90	10	45	120	20
PVC-110	50-110	SJSZ51/105	6	60	150	24
PVC-160	63-160	SJSZ65/132	5	100	300	24
PVC-250	110-250	SJSZ80/156	3.5	120	400	28
PVC-315	160-315	SJSZ80/156	3	160	400	36
PVC-450	250-450	SJSZ92/188	1.5	200	700	36
PVC-630	315-630	SJSZ92/188	0.9	230	700	36

Machine details



300/600 hot cold mixer

Final material: PVC and additives mixed powder

Mixing type: Heating and cooling

Total Volume: 300/600L (heating/cooling)
Valid Volume: 225 / 360L (heating/cooling)
Rotation speed of stirring blade: 500/1000/100 r/min

Heating mode: Electricity/ self-friction

Mixing time: 6-10min
Cooling time: 10-15min

SJSZ 65/132 twin conical screw extruder

screw & barrel: model: SJSZ-65/132 screw

main motor: 37 kw extruder output: 250 kg/h

feedere: double screw feeder

vacuum pump power: 3 kw inverter brand: Delta / ABB electrical parts: Siemens





PVC pipe mould PVC pipe size: 50-200 mm heater: ceramic heat ceramic heater

vacuum tank:

length: 6m

vacuum pump power: 4kw x 2 water pump power: 4 kw

water level control: automatic control movement distance: 600 mm movement motor power: 1.1 kw





3 - claw haul off machine inverter brand: ABB / Delta electical parts: Siemens



non dust cutter cutting range: 50-200 mm



fiber laser printer

Our customer&exhibition







Packing

THE COMPANY'S PRODUCTS ARE EXPORTED TO MIDDLE EAST, AFRICA, SOUTH AMERICA, SOUTH-EAST ASIA, RUSSIA AND OTHER COUNTRIES.





















Cingdao Changyue Plastic Machinery Co., Ltd.



0086 13705428176



edward@hualideplast.com



plasticextrudersmachine.com