


16-63 Mm Two Cavity Pvc Dual Contuit Pipe Production Line Customized For Business

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Packaging Details:



- CE, ISO9001:2008
 - Export Film Packing / According To Customer



Product Specification

- Model NO.:
- Automation:
- Computerized:
- Customized:
- Condition:
- After-sales Service:
- Extruder Size:
- Cavity:
- Pipe Diameter:
- Machine Output:
- Loading Port:
- Delivery Time:
- Transport Package:
- Specification:





More Images









Product Description

PVC DOUBLE PIPE EXTRUSION MACHINERY LINE

PVC double conduit pipe making machine

PVC double pipe extrusion line

Competitive Price for PVC UPVC pipes manufacturing machine/ PVC pipe production line/PVC pipes making machine High quality CPVC pipe extruder/ production line/ extrusion machinery

PVC CPVC UPVC pipes extrusion machine line

PVC pipe manufacturing production line/extruder machine

PVC pipes making machine line

pvc electric conduit pipe extruder machine

PVC conduit Pipe Production Line

Model	Pipe Diameter	Output	Max Speed	Motor	Total Length
SJSZ-65/132	50-75mm	250-350 kg/h	6m/min*2	30kw	22m
SJSZ-80/156	50-110mm	500-750kg/h	8m/min*2	55kw	23m

Features of the complete extrusion line

* Compact design takes up less room and enables a flexible layout of the assembly line.

* State-of-the art design gives the machines exclusive advantages of high productivity and superb cost efficiency.

* Customer-oriented design can meet specific requirement of different customers.

* All-around technical and comprehensive supports before and after sale services ensure a smooth and carefree operation of this line.

* A number of adoptions of automation can precisely control the process thus resulting in a solid quality of final product.

Siemens PLC control

Detailed Photos



Twin screw extruder

Motor power: 37KW World famous brand electrical component such as Siemens,, ABB etc; High torque gearbox with adopts NSK/ bearing; Siemens original motor achieved global after service; Bimetallic screw and barrel PLC intelligent control system

Doube strand extrusion die head two cavity mould

- 1. Each channel after heat treatment, mirror polishing and chroming to ensure material flow smoothly.
- 2. Die head is modular design, easy for changing pipe sizes, assembling, dismantle and maintenance.
- 3. Body made of 40Cr with inner surface Chrome plating in and bush made of 40Cr with polished and Chrome plating Calibration sleeves: stainless steel or cooper
- 4. Heating body: aluminum






Vacuum calibration cooling tank:

- 1. Material: stainless steel SUS304
- 2. Water pump, 2x3kw
- 3. Vacuum pump 2X3kw
- 4. Vacuum pump connect type: piping coupling
- 5. The two water pumps work complementarily.

Doube Haul off Machine

- 1. Useful Haul-off length:1200mm
- 2. Haul-off motor power: 0.75wX2pcs motor
- 3. Haul-off speed:0.5-10m/min
- 4. Equipped with coder to give fixed length signal





Double Dust Free Cutter

- 1. Material of cutting blade: alloy steel
- 2. Cutting Motor power: 0.75KWX2pcs
- 3. Electrical parts: Delixi
- 4. PLC Control:Mitsu
- 5. Manual operation and automatic for optional

Certifications



exbitions & customers




Packaging &

Shipping



After Sales

Service



🔇 昌岳塑机 Qingdao Changyue Plastic Machinery Co., Ltd.

0086 13705428176

edward@hualideplast.com

© plasticextrudersmachine.com

SOUTH LONGYI ROAD, NO.2 JIAOXI INDUSTRIAL ZONE, JIAOZHOU CITY, QIGNDAO, CHINA